

KBBE 106/76 - 200		g=	9,89	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	28,8	m	
Armering:		MRd	2615,30	kNm	qRd					286,63	217,13	169,48	135,40							kN/m
		Mrev	1767,09	kNm	qrev					190,46	143,50	111,31	88,28							kN/m
		Moo	1384,35	kNm	qoo					147,07	110,28	85,06	67,02							kN/m
Sl. Arm.	As:	Mbal	897,64	kNm	qbal					91,88	68,03	51,68	39,98							kN/m
	0	VRd	1831,41	kN																
Liner	L 12,5 :	d	984,5	mm	ulev					-9,5	-12,0	-14,8	-17,6							mm
top	4				uoo					-0,6	-0,6	-0,6	-0,5							mm
hylde	1	At	4,26E+05	mm ²	u10kort					0,4	0,7	1,1	1,7							mm
bund	22	y	472,2	mm	u10lang					0,9	1,6	2,5	3,9							mm
		lk	4,29E+10	mm ⁴																
KBBE 106/76 - 200		g=	9,89	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	28,8	m	
Armering:		MRd	3218,30	kNm	qRd					269,47	210,84	168,90	114,27							kN/m
		Mrev	2258,43	kNm	qrev					186,15	145,01	115,58	77,24							kN/m
		Moo	1860,49	kNm	qoo					151,61	117,71	93,47	61,89							kN/m
Sl. Arm.	As:	Mbal	1244,21	kNm	qbal					98,11	75,45	59,23	38,11							kN/m
	0	VRd	1804,35	kN																
Liner	L 12,5 :	d	970,0	mm	ulev					-17,0	-21,1	-25,4	-34,5							mm
top	4				uoo					-1,8	-2,1	-2,4	-2,8							mm
hylde	1	At	4,30E+05	mm ²	u10kort					0,7	1,1	1,7	3,4							mm
bund	30	y	469,0	mm	u10lang					1,6	2,5	3,8	7,9							mm
		lk	4,34E+10	mm ⁴																
KBBE 106/76 - 200		g=	9,89	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	28,8	m	
Armering:		MRd	3685,01	kNm	qRd					242,85	194,83	132,28	94,56							kN/m
		Mrev	2702,08	kNm	qrev					175,44	140,22	94,36	66,70							kN/m
		Moo	2291,97	kNm	qoo					147,31	117,44	78,53	55,07							kN/m
Sl. Arm.	As:	Mbal	1544,22	kNm	qbal					96,02	75,90	49,69	33,88							kN/m
	0	VRd	1773,02	kN																
Liner	L 12,5 :	d	953,2	mm	ulev					-26,5	-32,0	-44,1	-56,7							mm
top	4				uoo					-3,1	-3,6	-4,5	-4,9							mm
hylde	1	At	4,34E+05	mm ²	u10kort					1,1	1,6	3,4	6,3							mm
bund	38	y	466,2	mm	u10lang					2,5	3,8	7,8	14,5							mm
		lk	4,37E+10	mm ⁴																
KBBE 106/76 - 200		g=	9,89	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	28,8	m	
Armering:		MRd	4026,14	kNm	qRd					266,25	213,78	145,44	104,23							kN/m
		Mrev	2900,95	kNm	qrev					189,08	151,27	102,03	72,34							kN/m
		Moo	2456,96	kNm	qoo					158,62	126,61	84,90	59,75							kN/m
Sl. Arm.	As:	Mbal	1615,36	kNm	qbal					100,90	79,85	52,43	35,90							kN/m
	1963	VRd	1773,02	kN																
Liner	L 12,5 :	d	953,2	mm	ulev					-26,1	-31,6	-43,6	-56,2							mm
top	4				uoo					-2,1	-2,4	-2,8	-2,7							mm
hylde	1	At	4,44E+05	mm ²	u10kort					1,0	1,5	3,2	5,9							mm
bund	38	y	478,8	mm	u10lang					2,3	3,6	7,4	13,7							mm
		lk	4,66E+10	mm ⁴																

KBBE 116/76 - 200				g=	11,42	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	28,8	m
Armering:		MRd	3150,76	kNm	qRd					262,08	204,68	163,62	110,13					kN/m			
		Mrev	2107,31	kNm	qrev					171,50	133,11	105,65	69,88					kN/m			
		Moo	1638,81	kNm	qoo					130,83	100,98	79,62	51,80					kN/m			
Sl. Arm.	As:	Mbal	1092,44	kNm	qbal					83,41	63,50	49,27	30,72					kN/m			
	0	VRd	2008,97	kN																	
Liner	L 12,5 :	d	1080,0	mm	ulev					-10,9	-13,5	-16,1	-21,3					mm			
top	4				uoo					-1,0	-1,2	-1,3	-1,2					mm			
hylde	1	At	4,91E+05	mm ²	u10kort					0,5	0,8	1,2	2,6					mm			
bund	24	y	516,8	mm	u10lang					1,2	1,9	2,9	5,9					mm			
		lk	5,77E+10	mm ⁴																	
KBBE 116/76 - 200				g=	11,42	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	28,8	m
Armering:		MRd	3833,49	kNm	qRd					251,50	201,55	136,47	97,24					kN/m			
		Mrev	2643,17	kNm	qrev					169,86	135,42	90,55	63,50					kN/m			
		Moo	2158,00	kNm	qoo					136,59	108,46	71,83	49,74					kN/m			
Sl. Arm.	As:	Mbal	1475,30	kNm	qbal					89,76	70,54	45,49	30,39					kN/m			
	0	VRd	1981,06	kN																	
Liner	L 12,5 :	d	1065,0	mm	ulev					-18,6	-22,5	-30,6	-38,8					mm			
top	4				uoo					-2,5	-2,9	-3,6	-3,9					mm			
hylde	1	At	4,95E+05	mm ²	u10kort					0,8	1,2	2,6	4,7					mm			
bund	32	y	513,7	mm	u10lang					1,9	2,8	5,9	10,9					mm			
		lk	5,83E+10	mm ⁴																	
KBBE 116/76 - 200				g=	11,42	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	28,8	m
Armering:		MRd	4393,38	kNm	qRd					232,65	158,07	113,10	83,92					kN/m			
		Mrev	3142,19	kNm	qrev					163,14	109,80	77,64	56,77					kN/m			
		Moo	2642,70	kNm	qoo					135,39	90,53	63,48	45,93					kN/m			
Sl. Arm.	As:	Mbal	1821,74	kNm	qbal					89,78	58,86	40,21	28,11					kN/m			
	0	VRd	1953,16	kN																	
Liner	L 12,5 :	d	1050,0	mm	ulev					-28,2	-38,8	-50,0	-61,0					mm			
top	4				uoo					-4,1	-5,4	-6,3	-6,7					mm			
hylde	1	At	4,99E+05	mm ²	u10kort					1,2	2,5	4,7	8,0					mm			
bund	40	y	510,9	mm	u10lang					2,8	5,8	10,8	18,5					mm			
		lk	5,88E+10	mm ⁴																	
KBBE 116/76 - 200				g=	11,42	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	28,8	m
Armering:		MRd	4748,25	kNm	qRd					252,37	171,76	123,16	91,62					kN/m			
		Mrev	3354,85	kNm	qrev					174,96	118,01	83,67	61,38					kN/m			
		Moo	2816,36	kNm	qoo					145,04	97,23	68,40	49,69					kN/m			
Sl. Arm.	As:	Mbal	1893,57	kNm	qbal					93,77	61,63	42,25	29,67					kN/m			
	1963	VRd	1953,16	kN																	
Liner	L 12,5 :	d	1050,0	mm	ulev					-27,8	-38,3	-49,5	-60,5					mm			
top	4				uoo					-3,1	-3,8	-4,3	-4,2					mm			
hylde	1	At	5,09E+05	mm ²	u10kort					1,2	2,4	4,4	7,6					mm			
bund	40	y	523,0	mm	u10lang					2,7	5,5	10,2	17,4					mm			
		lk	6,23E+10	mm ⁴																	

KBBE 126/76 - 200		g=	12,99	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	28,8	m
Armering:		MRd	3743,59	kNm	qRd				311,98	243,78	194,99	131,44							kN/m
		Mrev	2484,53	kNm	qrev				202,68	157,42	125,04	82,87							kN/m
		Moo	1923,81	kNm	qoo				154,01	118,96	93,89	61,23							kN/m
Sl. Arm.	As:	Mbal	1321,18	kNm	qbal				101,70	77,63	60,41	37,98							kN/m
	0	VRd	2187,83	kN															
Liner	L 12,5 :	d	1176,2	mm	ulev				-10,2	-12,5	-15,0	-20,0							mm
top	4				uoo				-1,4	-1,7	-1,9	-2,2							mm
hylde	1	At	5,57E+05	mm ²	u10kort				0,4	0,6	1,0	2,0							mm
bund	26	y	563,8	mm	u10lang				0,9	1,4	2,2	4,5							mm
		lk	7,56E+10	mm ⁴															
KBBE 126/76 - 200		g=	12,99	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	28,8	m
Armering:		MRd	4506,66	kNm	qRd					296,11	237,38	160,88	114,75						kN/m
		Mrev	3066,07	kNm	qrev					197,31	157,35	105,30	73,92						kN/m
		Moo	2487,16	kNm	qoo					157,60	125,19	82,97	57,51						kN/m
Sl. Arm.	As:	Mbal	1742,88	kNm	qbal					106,55	83,84	54,25	36,41						kN/m
	0	VRd	2158,87	kN															
Liner	L 12,5 :	d	1160,6	mm	ulev					-16,9	-20,4	-27,8	-35,4						mm
top	4				uoo					-2,9	-3,4	-4,4	-5,1						mm
hylde	1	At	5,61E+05	mm ²	u10kort					0,6	0,9	2,0	3,6						mm
bund	34	y	560,9	mm	u10lang					1,4	2,2	4,5	8,3						mm
		lk	7,62E+10	mm ⁴															
KBBE 126/76 - 200		g=	12,99	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	28,8	m
Armering:		MRd	5152,08	kNm	qRd						273,24	185,78	133,05	98,82					kN/m
		Mrev	3613,86	kNm	qrev						187,78	126,44	89,45	65,44					kN/m
		Moo	3018,92	kNm	qoo						154,73	103,48	72,58	52,53					kN/m
Sl. Arm.	As:	Mbal	2130,74	kNm	qbal						105,39	69,22	47,41	33,25					kN/m
	0	VRd	2131,20	kN															
Liner	L 12,5 :	d	1145,7	mm	ulev						-25,3	-34,9	-45,0	-55,0					mm
top	4				uoo						-4,6	-6,1	-7,4	-8,4					mm
hylde	1	At	5,65E+05	mm ²	u10kort						0,9	1,9	3,6	6,1					mm
bund	42	y	558,1	mm	u10lang						2,2	4,5	8,3	14,1					mm
		lk	7,68E+10	mm ⁴															
KBBE 126/76 - 200		g=	12,99	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	28,8	m
Armering:		MRd	5520,61	kNm	qRd						293,71	200,00	143,49	106,82					kN/m
		Mrev	3838,14	kNm	qrev						200,24	135,09	95,80	70,31					kN/m
		Moo	3199,53	kNm	qoo						164,76	110,45	77,70	56,45					kN/m
Sl. Arm.	As:	Mbal	2203,20	kNm	qbal						109,41	72,01	49,46	34,83					kN/m
	1963	VRd	2131,20	kN															
Liner	L 12,5 :	d	1145,7	mm	ulev						-24,9	-34,4	-44,4	-54,5					mm
top	4				uoo						-3,7	-4,7	-5,6	-6,1					mm
hylde	1	At	5,75E+05	mm ²	u10kort						0,9	1,8	3,4	5,8					mm
bund	42	y	569,8	mm	u10lang						2,0	4,2	7,9	13,4					mm
		lk	8,10E+10	mm ⁴															

KBBE 136/76 - 200				g=	14,58	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	28,8	m
Armering:		MRd	4394,45	kNm	qRd					286,82	229,56	154,96	109,98					kN/m			
		Mrev	2900,85	kNm	qrev					184,38	146,58	97,34	67,64					kN/m			
		Moo	2240,41	kNm	qoo					139,08	109,89	71,86	48,92					kN/m			
Sl. Arm.	As:	Mbal	1582,88	kNm	qbal					93,98	73,36	46,49	30,29					kN/m			
	0	VRd	2367,71	kN																	
Liner	L 12,5 :	d	1272,9	mm	ulev					-11,8	-14,2	-19,0	-23,7					mm			
top	4				uoo					-2,1	-2,5	-3,1	-3,4					mm			
hylde	1	At	6,24E+05	mm ²	u10kort					0,5	0,7	1,5	2,9					mm			
bund	28	y	612,8	mm	u10lang					1,1	1,7	3,5	6,6					mm			
		lk	9,69E+10	mm ⁴																	
KBBE 136/76 - 200				g=	14,58	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	28,8	m
Armering:		MRd	5238,41	kNm	qRd					276,44	187,52	133,90	99,10					kN/m			
		Mrev	3529,28	kNm	qrev					181,49	121,58	85,46	62,01					kN/m			
		Moo	2849,08	kNm	qoo					143,70	95,34	66,18	47,25					kN/m			
Sl. Arm.	As:	Mbal	2045,28	kNm	qbal					99,05	64,33	43,39	29,81					kN/m			
	0	VRd	2337,59	kN																	
Liner	L 12,5 :	d	1256,7	mm	ulev					-18,8	-25,7	-32,8	-39,5					mm			
top	4				uoo					-3,8	-5,0	-6,1	-6,8					mm			
hylde	1	At	6,28E+05	mm ²	u10kort					0,7	1,5	2,8	4,8					mm			
bund	36	y	609,9	mm	u10lang					1,7	3,5	6,5	11,1					mm			
		lk	9,77E+10	mm ⁴																	
KBBE 136/76 - 200				g=	14,58	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	28,8	m
Armering:		MRd	5969,86	kNm	qRd					215,74	154,63	114,97	87,78					kN/m			
		Mrev	4126,96	kNm	qrev					144,64	102,40	74,98	56,18					kN/m			
		Moo	3428,96	kNm	qoo					117,71	82,61	59,83	44,22					kN/m			
Sl. Arm.	As:	Mbal	2476,43	kNm	qbal					80,96	55,61	39,16	27,88					kN/m			
	0	VRd	2309,97	kN																	
Liner	L 12,5 :	d	1241,8	mm	ulev					-31,8	-41,1	-50,4	-59,1					mm			
top	4				uoo					-6,6	-8,3	-9,7	-10,6					mm			
hylde	1	At	6,32E+05	mm ²	u10kort					1,5	2,8	4,8	7,7					mm			
bund	44	y	607,2	mm	u10lang					3,5	6,5	11,0	17,7					mm			
		lk	9,84E+10	mm ⁴																	
KBBE 136/76 - 200				g=	14,58	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	28,8	m
Armering:		MRd	6352,11	kNm	qRd					230,49	165,47	123,27	94,34					kN/m			
		Mrev	4361,13	kNm	qrev					153,67	109,03	80,06	60,20					kN/m			
		Moo	3615,18	kNm	qoo					124,89	87,89	63,87	47,41					kN/m			
Sl. Arm.	As:	Mbal	2549,50	kNm	qbal					83,78	57,68	40,75	29,14					kN/m			
	1963	VRd	2309,97	kN																	
Liner	L 12,5 :	d	1241,8	mm	ulev					-31,3	-40,6	-49,9	-58,6					mm			
top	4				uoo					-5,5	-6,7	-7,7	-8,2					mm			
hylde	1	At	6,43E+05	mm ²	u10kort					1,4	2,7	4,6	7,3					mm			
bund	44	y	618,5	mm	u10lang					3,3	6,2	10,5	16,8					mm			
		lk	1,03E+11	mm ⁴																	

KBBE 146/76 - 200				g=	16,20	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	m
Armering:		MRd	5103,98	kNm	qRd					333,86	267,35	180,71	128,47					kN/m		
		Mrev	3357,60	kNm	qrev					214,08	170,33	113,33	78,97					kN/m		
		Moo	2589,14	kNm	qoo					161,38	127,64	83,69	57,19					kN/m		
Sl. Arm.	As:	Mbal	1876,93	kNm	qbal					112,53	88,07	56,21	37,00					kN/m		
	0	VRd	2548,41	kN																
Liner	L 12,5 :	d	1370,0	mm	ulev					-11,2	-13,5	-18,2	-22,8					mm		
top	4				uoo					-2,4	-2,9	-3,7	-4,4					mm		
hylde	1	At	6,93E+05	mm ²	u10kort					0,4	0,6	1,2	2,3					mm		
bund	30	y	663,1	mm	u10lang					0,9	1,4	2,8	5,2					mm		
		lk	1,22E+11	mm ⁴																
KBBE 146/76 - 200				g=	16,20	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	m
Armering:		MRd	6029,33	kNm	qRd					318,76	216,41	154,70	114,64					kN/m		
		Mrev	4034,06	kNm	qrev					207,91	139,43	98,14	71,34					kN/m		
		Moo	3244,23	kNm	qoo					164,03	108,96	75,75	54,20					kN/m		
Sl. Arm.	As:	Mbal	2381,48	kNm	qbal					116,10	75,68	51,30	35,48					kN/m		
	0	VRd	2517,08	kN																
Liner	L 12,5 :	d	1353,2	mm	ulev					-17,5	-23,9	-30,6	-37,1					mm		
top	4				uoo					-4,1	-5,5	-6,8	-7,9					mm		
hylde	1	At	6,97E+05	mm ²	u10kort					0,6	1,2	2,2	3,8					mm		
bund	38	y	660,3	mm	u10lang					1,3	2,8	5,2	8,8					mm		
		lk	1,23E+11	mm ⁴																
KBBE 146/76 - 200				g=	16,20	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	m
Armering:		MRd	6847,27	kNm	qRd					247,97	177,88	132,39	101,21					kN/m		
		Mrev	4682,67	kNm	qrev					164,46	116,53	85,42	64,09					kN/m		
		Moo	3873,24	kNm	qoo					133,23	93,58	67,85	50,21					kN/m		
Sl. Arm.	As:	Mbal	2857,33	kNm	qbal					94,03	64,79	45,81	32,79					kN/m		
	0	VRd	2489,37	kN																
Liner	L 12,5 :	d	1338,3	mm	ulev					-29,3	-38,0	-46,7	-54,9					mm		
top	4				uoo					-7,0	-8,9	-10,6	-12,0					mm		
hylde	1	At	7,01E+05	mm ²	u10kort					1,2	2,2	3,8	6,1					mm		
bund	46	y	657,6	mm	u10lang					2,8	5,1	8,8	14,0					mm		
		lk	1,24E+11	mm ⁴																
KBBE 146/76 - 200				g=	16,20	kN/m	længde:		7,2	8,4	9,6	10,8	12,0	14,4	16,8	19,2	21,6	24,0	26,4	m
Armering:		MRd	7243,32	kNm	qRd					263,25	189,11	140,99	108,00					kN/m		
		Mrev	4925,38	kNm	qrev					173,82	123,41	90,68	68,25					kN/m		
		Moo	4064,07	kNm	qoo					140,59	98,99	71,99	53,48					kN/m		
Sl. Arm.	As:	Mbal	2931,04	kNm	qbal					96,88	66,88	47,40	34,05					kN/m		
	1963	VRd	2489,37	kN																
Liner	L 12,5 :	d	1338,3	mm	ulev					-28,8	-37,4	-46,1	-54,4					mm		
top	4				uoo					-6,0	-7,5	-8,9	-9,8					mm		
hylde	1	At	7,11E+05	mm ²	u10kort					1,2	2,1	3,6	5,8					mm		
bund	46	y	668,5	mm	u10lang					2,7	4,9	8,4	13,4					mm		
		lk	1.30E+11	mm ⁴																