

Bæreevnetabel

22-06-2021

RB 50/54		g=	6,48	kN/m	længde:	2,4	3,6	4,8	6,0	7,2	8,4	9,6	10,8	12,0	13,2	14,4	15,6	m
Armering:		MRd	884,42	kNm	qRd					130,00	93,79	70,29	54,18					kN/m
		Mrev	578,63	kNm	qrev					82,81	59,12	43,75	33,21					kN/m
		Moo	460,34	kNm	qoo					64,56	45,71	33,48	25,09					kN/m
Sl. Arm.	As	Mbal	305,40	kNm	qbal					40,65	28,15	20,03	14,47					kN/m
	0	VRd	453,11	kN														kN/m
Liner top	L 12,5 : 4	d	475	mm	ulev					-14,0	-18,2	-22,5	-26,6					mm
					uoo					-1,2	-1,3	-1,3	-0,9					mm
midtbund	0 16	At	2,80E+05	mm ²	u10kort					1,3	2,5	4,2	6,8					mm
		y	265,7	mm	u10lang					3,1	5,7	9,7	15,5					mm
		lk	7,00E+09	mm ⁴														
RB 50/54		g=	6,48	kN/m	længde:	2,4	3,6	4,8	6,0	7,2	8,4	9,6	10,8	12,0	13,2	14,4	15,6	m
Armering:		MRd	1034,03	kNm	qRd						110,76	83,28	64,44	50,97				kN/m
		Mrev	696,46	kNm	qrev						72,48	53,98	41,29	32,21				kN/m
		Moo	574,63	kNm	qoo						58,67	43,40	32,93	25,44				kN/m
Sl. Arm.	As	Mbal	394,19	kNm	qbal						38,21	27,74	20,56	15,42				kN/m
	0	VRd	448,34	kN														kN/m
Liner top	L 12,5 : 4	d	470	mm	ulev						-24,2	-30,3	-36,6	-42,6				mm
					uoo						-3,2	-3,8	-4,2	-4,2				mm
midtbund	0 20	At	2,82E+05	mm ²	u10kort						2,4	4,2	6,7	10,2				mm
		y	264,4	mm	u10lang						5,6	9,6	15,4	23,5				mm
		lk	7,06E+09	mm ⁴														
RB 50/54		g=	6,48	kN/m	længde:	2,4	3,6	4,8	6,0	7,2	8,4	9,6	10,8	12,0	13,2	14,4	15,6	m
Armering:		MRd	1126,19	kNm	qRd							91,28	70,76	56,09	45,23			kN/m
		Mrev	771,62	kNm	qrev							60,50	46,44	36,39	28,95			kN/m
		Moo	646,28	kNm	qoo							49,62	37,85	29,42	23,19			kN/m
Sl. Arm.	As	Mbal	405,01	kNm	qbal							28,68	21,30	16,02	12,12			kN/m
	0	VRd	438,81	kN														kN/m
Liner top	L 12,5 : 6	d	460	mm	ulev							-30,9	-37,3	-43,6	-49,5			mm
					uoo							0,7	1,5	2,8	4,5			mm
midtbund	0 24	At	2,85E+05	mm ²	u10kort							4,1	6,6	10,1	14,8			mm
		y	264,3	mm	u10lang							9,5	15,2	23,2	33,9			mm
		lk	7,14E+09	mm ⁴														
RB 50/54		g=	6,48	kN/m	længde:	2,4	3,6	4,8	6,0	7,2	8,4	9,6	10,8	12,0	13,2	14,4	15,6	m
Armering:		MRd	1175,20	kNm	qRd								74,12	58,81	47,48	38,86		kN/m
		Mrev	819,57	kNm	qrev								49,73	39,05	31,15	25,14		kN/m
		Moo	693,09	kNm	qoo								41,06	32,03	25,34	20,26		kN/m
Sl. Arm.	As	Mbal	438,46	kNm	qbal								23,59	17,88	13,65	10,44		kN/m
	0	VRd	435,14	kN														kN/m
Liner top	L 12,5 : 6	d	456	mm	ulev								-41,0	-48,2	-55,0	-61,1		mm
					uoo									0,7	1,8	3,3	5,4	mm
midtbund	0 26	At	2,86E+05	mm ²	u10kort								6,6	10,1	14,7	20,8		mm
		y	263,8	mm	u10lang									15,2	23,1	33,9	47,9	mm
		lk	7,16E+09	mm ⁴														

Bæreevnetabel

22-06-2021

RB 50/60			g=	7,20	kN/m	længde:	4,8	6,0	7,2	8,4	9,6	10,8	12,0	13,2	14,4	15,6	16,8	18,0	m			
Armering:		MRd	1117,22	kNm		qRd				119,47	89,78	69,43	54,87							kN/m		
		Mrev	728,21	kNm		qrev				75,36	56,01	42,75	33,26								kN/m	
		Moo	589,60	kNm		qoo				59,65	43,98	33,24	25,56								kN/m	
Sl. Arm.	As	Mbal	404,81	kNm		qbal				38,70	27,94	20,56	15,29								kN/m	
	0	VRd	507,70	kN																		
Liner top	L 12,5 : 4	d	532	mm		ulev				-18,0	-22,5	-27,0	-31,3								mm	
						uoo				-2,4	-2,8	-3,0	-3,0									mm
midtbund	0 18	At	3,11E+05	mm ²		u10kort				1,8	3,1	4,9	7,5								mm	
		y	294,9	mm		u10lang				4,1	7,1	11,3	17,2									mm
		lk	9,61E+09	mm ⁴																		
RB 50/60			g=	7,20	kN/m	længde:	4,8	6,0	7,2	8,4	9,6	10,8	12,0	13,2	14,4	15,6	16,8	18,0	m			
Armering:		MRd	1278,16	kNm		qRd					103,75	80,47	63,81	51,49							kN/m	
		Mrev	854,06	kNm		qrev					66,94	51,38	40,25	32,01								kN/m
		Moo	712,03	kNm		qoo					54,61	41,64	32,36	25,49								kN/m
Sl. Arm.	As	Mbal	498,32	kNm		qbal				36,06	26,98	20,48	15,68									kN/m
	0	VRd	500,38	kN																		
Liner top	L 12,5 : 4	d	525	mm		ulev					-28,6	-34,7	-40,8	-46,6							mm	
						uoo					-4,6	-5,3	-5,8	-6,1								mm
midtbund	0 22	At	3,13E+05	mm ²		u10kort					3,0	4,9	7,4	10,9							mm	
		y	293,7	mm		u10lang					7,0	11,2	17,1	25,0								mm
		lk	9,68E+09	mm ⁴																		
RB 50/60			g=	7,20	kN/m	længde:	4,8	6,0	7,2	8,4	9,6	10,8	12,0	13,2	14,4	15,6	16,8	18,0	m			
Armering:		MRd	1391,01	kNm		qRd						88,21	70,08	56,67	46,47						kN/m	
		Mrev	943,62	kNm		qrev						57,52	45,22	36,13	29,21							kN/m
		Moo	797,44	kNm		qoo						47,49	37,10	29,41	23,57							kN/m
Sl. Arm.	As	Mbal	516,11	kNm		qbal					28,20	21,47	16,50	12,71								kN/m
	0	VRd	492,37	kN																		
Liner top	L 12,5 : 6	d	516	mm		ulev						-35,7	-42,1	-48,2	-53,9						mm	
						uoo						-0,9	-0,4	0,4	1,7							mm
midtbund	0 26	At	3,16E+05	mm ²		u10kort						4,8	7,3	10,8	15,2						mm	
		y	293,4	mm		u10lang						11,1	16,9	24,7	35,0							mm
		lk	9,80E+09	mm ⁴																		
RB 50/60			g=	7,20	kN/m	længde:	4,8	6,0	7,2	8,4	9,6	10,8	12,0	13,2	14,4	15,6	16,8	18,0	m			
Armering:		MRd	1507,73	kNm		qRd							76,56	62,03	50,97	42,36					kN/m	
		Mrev	1057,10	kNm		qrev								51,53	41,34	33,58	27,55					kN/m
		Moo	908,15	kNm		qoo								43,25	34,50	27,84	22,65					kN/m
Sl. Arm.	As	Mbal	597,48	kNm		qbal								25,99	20,23	15,85	12,44					kN/m
	0	VRd	486,50	kN																		
Liner top	L 12,5 : 6	d	510	mm		ulev							-50,1	-58,0	-65,5	-72,4					mm	
						uoo								-2,5	-2,1	-1,2	0,1					mm
midtbund	0 30	At	3,18E+05	mm ²		u10kort							7,3	10,7	15,2	20,9					mm	
		y	292,4	mm		u10lang								16,8	24,6	34,9	48,0					mm
		lk	9,85E+09	mm ⁴																		

Bæreevnetabel

22-06-2021

RB 50/72			g=	8,64	kN/m	længde:	6,0	7,2	8,4	9,6	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	m			
Armering:		MRd	1658,12	kNm	qRd					135,29	105,09	83,48	67,49							kN/m		
		Mrev	1092,52	kNm	qrev					86,20	66,29	52,06	41,52								kN/m	
		Moo	891,46	kNm	qoo					68,74	52,50	40,89	32,29								kN/m	
Sl. Arm.	As	Mbal	639,38	kNm	qbal				46,86	35,21	26,88	20,72									kN/m	
	0	VRd	614,85	kN																		
Liner	L 12,5 :	d	645	mm	ulev					-21,5	-26,2	-31,0	-35,6								mm	
		4			uoo					-4,3	-5,0	-5,7	-6,3									mm
midt	0	At	3,73E+05	mm ²	u10kort					1,8	2,8	4,3	6,3								mm	
bund	22	y	353,2	mm	u10lang					4,1	6,5	10,0	14,6								mm	
		lk	1,66E+10	mm ⁴																		
RB 50/72			g=	8,64	kN/m	længde:	6,0	7,2	8,4	9,6	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	m			
Armering:		MRd	1735,66	kNm	qRd						110,40	87,79	71,05	58,32							kN/m	
		Mrev	1135,94	kNm	qrev						69,27	54,47	43,52	35,19								kN/m
		Moo	931,08	kNm	qoo						55,22	43,09	34,11	27,28								kN/m
Sl. Arm.	As	Mbal	615,67	kNm	qbal					33,59	25,56	19,63	15,11									kN/m
	0	VRd	610,51	kN																		
Liner	L 12,5 :	d	640	mm	ulev					-24,8	-29,3	-33,5	-37,5									mm
		6			uoo					-1,5	-1,4	-1,0	-0,4									mm
midt	0	At	3,75E+05	mm ²	u10kort					2,8	4,3	6,3	8,9									mm
bund	24	y	353,5	mm	u10lang					6,5	9,9	14,4	20,5									mm
		lk	1,68E+10	mm ⁴																		
RB 50/72			g=	8,64	kN/m	længde:	6,0	7,2	8,4	9,6	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	m			
Armering:		MRd	1920,48	kNm	qRd							98,05	79,54	65,45	54,49						kN/m	
		Mrev	1287,94	kNm	qrev							62,91	50,49	41,05	33,70							kN/m
		Moo	1078,92	kNm	qoo							51,30	40,90	32,98	26,83							kN/m
Sl. Arm.	As	Mbal	728,31	kNm	qbal						31,82	24,80	19,46	15,30								kN/m
	0	VRd	603,70	kN																		
Liner	L 12,5 :	d	633	mm	ulev							-35,8	-41,4	-46,8	-51,9							mm
		6			uoo							-3,3	-3,4	-3,2	-2,6							mm
midt	0	At	3,77E+05	mm ²	u10kort						4,3	6,2	8,8	12,2								mm
bund	28	y	352,3	mm	u10lang						9,8	14,4	20,3	28,0								mm
		lk	1,69E+10	mm ⁴																		
RB 50/72			g=	8,64	kN/m	længde:	6,0	7,2	8,4	9,6	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	m			
Armering:		MRd	2078,84	kNm	qRd								86,81	71,56	59,70	50,28					kN/m	
		Mrev	1428,57	kNm	qrev								56,95	46,47	38,32	31,85						kN/m
		Moo	1216,02	kNm	qoo								47,19	38,27	31,33	25,83						kN/m
Sl. Arm.	As	Mbal	829,72	kNm	qbal							29,46	23,37	18,64	14,88							kN/m
	0	VRd	596,20	kN																		
Liner	L 12,5 :	d	625	mm	ulev								-48,4	-55,2	-61,7	-67,7						mm
		6			uoo								-5,2	-5,4	-5,2	-4,7						mm
midt	0	At	3,79E+05	mm ²	u10kort							6,2	8,8	12,1	16,3							mm
bund	32	y	351,2	mm	u10lang								14,3	20,2	27,9	37,5						mm
		lk	1,70E+10	mm ⁴																		

Bæreevnetabel

22-06-2021

RB 50/84				g=	10,08	kN/m	længde:	8,4	9,6	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	m	
Armering:		MRd	2177,24	kNm			qRd					89,89	73,92	61,49	51,63						kN/m
		Mrev	1434,38	kNm			qrev					55,78	45,26	37,07	30,58						kN/m
		Moo	1162,29	kNm			qoo					43,29	34,76	28,13	22,86						kN/m
Sl. Arm.	As	Mbal	853,11	kNm			qbal				29,09	22,83	17,96	14,10							kN/m
	0	VRd	628,32	kN																	
Liner top	L 12,5 : 4	d	760	mm			ulev					-31,1	-35,2	-39,0	-42,3						mm
							uoo					-6,8	-7,5	-8,0	-8,2						mm
midtbund	0 24	At	4,34E+05	mm ²			u10kort					4,0	5,7	7,8	10,5						mm
		y	412,2	mm			u10lang					9,2	13,0	17,9	24,1						mm
		lk	2,64E+10	mm ⁴																	
RB 50/84				g=	10,08	kN/m	længde:	8,4	9,6	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	m	
Armering:		MRd	2278,61	kNm			qRd						77,83	64,82	54,51	46,18					kN/m
		Mrev	1488,83	kNm			qrev						47,36	38,86	32,12	26,68					kN/m
		Moo	1211,84	kNm			qoo						36,67	29,76	24,27	19,84					kN/m
Sl. Arm.	As	Mbal	828,83	kNm			qbal					21,90	17,17	13,41	10,38						kN/m
	0	VRd	625,14	kN																	
Liner top	L 12,5 : 6	d	756	mm			ulev						-33,6	-37,1	-40,1	-42,5					mm
							uoo						-3,0	-2,7	-2,1	-1,2					mm
midtbund	0 26	At	4,36E+05	mm ²			u10kort						5,6	7,7	10,4	13,7					mm
		y	412,5	mm			u10lang						12,9	17,8	23,9	31,5					mm
		lk	2,66E+10	mm ⁴																	
RB 50/84				g=	10,08	kN/m	længde:	8,4	9,6	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	m	
Armering:		MRd	2489,39	kNm			qRd							71,75	60,48	51,39	43,94				kN/m
		Mrev	1639,37	kNm			qrev							43,81	36,39	30,40	25,50				kN/m
		Moo	1354,67	kNm			qoo							34,45	28,32	23,37	19,32				kN/m
Sl. Arm.	As	Mbal	876,15	kNm			qbal						18,72	14,75	11,55	8,93					kN/m
	0	VRd	620,05	kN																	
Liner top	L 12,5 : 8	d	750	mm			ulev							-39,7	-43,1	-46,0	-48,1				mm
							uoo							1,1	2,3	3,9	5,9				mm
midtbund	0 30	At	4,39E+05	mm ²			u10kort							7,6	10,3	13,6	17,6				mm
		y	412,0	mm			u10lang							17,6	23,7	31,2	40,4				mm
		lk	2,69E+10	mm ⁴																	
RB 50/84				g=	10,08	kN/m	længde:	8,4	9,6	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	m	
Armering:		MRd	2686,85	kNm			qRd								66,08	56,26	48,23	41,57			kN/m
		Mrev	1807,70	kNm			qrev								41,16	34,55	29,15	24,67			kN/m
		Moo	1518,70	kNm			qoo								32,97	27,42	22,88	19,11			kN/m
Sl. Arm.	As	Mbal	997,82	kNm			qbal							18,20	14,56	11,57	9,10				kN/m
	0	VRd	612,27	kN																	
Liner top	L 12,5 : 8	d	741	mm			ulev								-51,8	-55,9	-59,4	-61,9			mm
							uoo								0,0	1,2	2,9	5,1			mm
midtbund	0 34	At	4,41E+05	mm ²			u10kort								10,2	13,5	17,5	22,3			mm
		y	410,9	mm			u10lang								23,6	31,1	40,2	51,2			mm
		lk	2,70E+10	mm ⁴																	

Bæreevnetabel

22-06-2021

RB 50/96		g=	11,52	kN/m	længde:	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	m
Armering:		MRd	2281,66	kNm	qRd					63,49	53,15	44,82	38,00					kN/m
		Mrev	1481,12	kNm	qrev					37,17	30,46	25,05	20,62					kN/m
		Moo	1137,91	kNm	qoo					25,89	20,73	16,58	13,17					kN/m
Sl. Arm.	As	Mbal	834,34	kNm	qbal					15,91	12,13	9,08	6,59					kN/m
	0	VRd	735,79	kN														
Liner top	L 12,5 : 4	d	890	mm	ulev					-24,1	-25,6	-26,7	-27,0					mm
					uoo					-4,6	-4,6	-4,3	-3,7					mm
midtbund	0 20	At	4,92E+05	mm ²	u10kort					5,3	7,1	9,4	12,1					mm
		y	473,4	mm	u10lang					12,2	16,3	21,5	27,9					mm
		lk	3,89E+10	mm ⁴														
RB 50/96		g=	11,52	kN/m	længde:	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	m
Armering:		MRd	2736,56	kNm	qRd						66,05	56,05	47,87	41,09				kN/m
		Mrev	1773,95	kNm	qrev						38,76	32,28	26,98	22,58				kN/m
		Moo	1417,69	kNm	qoo						28,66	23,48	19,25	15,73				kN/m
Sl. Arm.	As	Mbal	985,93	kNm	qbal					16,43	12,82	9,88	7,43					kN/m
	0	VRd	724,35	kN														
Liner top	L 12,5 : 6	d	876	mm	ulev						-32,8	-34,9	-36,4	-37,1				mm
					uoo						-3,0	-2,5	-1,7	-0,5				mm
midtbund	0 26	At	4,96E+05	mm ²	u10kort						7,0	9,2	12,0	15,2				mm
		y	472,2	mm	u10lang						16,1	21,2	27,5	35,1				mm
		lk	3,95E+10	mm ⁴														
RB 50/96		g=	11,52	kN/m	længde:	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	m
Armering:		MRd	3137,78	kNm	qRd							65,96	56,57	48,80	42,28			kN/m
		Mrev	2057,48	kNm	qrev							39,28	33,13	28,03	23,76			kN/m
		Moo	1688,83	kNm	qoo							30,18	25,13	20,95	17,44			kN/m
Sl. Arm.	As	Mbal	1124,94	kNm	qbal						16,26	12,89	10,11	7,77				kN/m
	0	VRd	715,13	kN														
Liner top	L 12,5 : 8	d	865	mm	ulev							-42,3	-44,8	-46,7	-47,6			mm
					uoo							-0,2	1,0	2,5	4,4			mm
midtbund	0 32	At	5,00E+05	mm ²	u10kort							9,1	11,8	15,0	18,9			mm
		y	471,1	mm	u10lang							21,0	27,1	34,6	43,5			mm
		lk	4,00E+10	mm ⁴														
RB 50/96		g=	11,52	kN/m	længde:	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	m
Armering:		MRd	3388,09	kNm	qRd								62,01	53,61	46,57	40,62		kN/m
		Mrev	2262,74	kNm	qrev								37,58	31,98	27,28	23,30		kN/m
		Moo	1888,43	kNm	qoo								29,46	24,78	20,86	17,54		kN/m
Sl. Arm.	As	Mbal	1276,88	kNm	qbal							16,19	13,03	10,37	8,13			kN/m
	0	VRd	708,24	kN														
Liner top	L 12,5 : 8	d	857	mm	ulev								-54,3	-57,4	-59,6	-60,9		mm
					uoo									-1,9	-0,7	0,8	2,8	mm
midtbund	0 36	At	5,02E+05	mm ²	u10kort								11,7	15,0	18,8	23,4		mm
		y	469,8	mm	u10lang									27,0	34,4	43,3	53,7	mm
		lk	4,02E+10	mm ⁴														

Bæreevnetabel

22-06-2021

RB 50/108			g=	12,96	kN/m	længde:	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	26,4	m			
Armering:		MRd	2853,45	kNm	qRd					67,92	57,50	48,96	41,89							kN/m		
		Mrev	1859,39	kNm	qrev					39,74	32,95	27,39	22,78								kN/m	
		Moo	1426,07	kNm	qoo					27,46	22,25	17,99	14,45								kN/m	
Sl. Arm.	As	Mbal	1064,50	kNm	qbal					17,21	13,32	10,14	7,50								kN/m	
	0	VRd	830,49	kN																	kN/m	
Liner top	L 12,5 : 4	d	1005	mm	ulev					-24,7	-26,2	-27,1	-27,4								mm	
					uoo					-5,6	-5,6	-5,4	-5,0									mm
midtbund	0 22	At	5,53E+05	mm ²	u10kort					5,0	6,6	8,5	10,9								mm	
		y	532,5	mm	u10lang					11,5	15,1	19,6	25,0									mm
		lk	5,53E+10	mm ⁴																		
RB 50/108			g=	12,96	kN/m	længde:	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	26,4	m			
Armering:		MRd	3385,74	kNm	qRd						70,64	60,52	52,13	45,09							kN/m	
		Mrev	2199,78	kNm	qrev						41,36	34,78	29,33	24,76								kN/m
		Moo	1750,83	kNm	qoo						30,27	25,04	20,70	17,06								kN/m
Sl. Arm.	As	Mbal	1246,15	kNm	qbal					17,81	14,08	11,00	8,41									kN/m
	0	VRd	820,83	kN																		kN/m
Liner top	L 12,5 : 6	d	993	mm	ulev					-33,2	-35,1	-36,4	-37,1								mm	
					uoo					-4,5	-4,2	-3,6	-2,7									mm
midtbund	0 28	At	5,57E+05	mm ²	u10kort					6,5	8,4	10,7	13,5								mm	
		y	531,2	mm	u10lang					14,9	19,4	24,7	31,0									mm
		lk	5,61E+10	mm ⁴																		
RB 50/108			g=	12,96	kN/m	længde:	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	26,4	m			
Armering:		MRd	3852,44	kNm	qRd							70,64	61,10	53,10	46,33						kN/m	
		Mrev	2521,12	kNm	qrev							41,75	35,50	30,27	25,84							kN/m
		Moo	2057,92	kNm	qoo							31,70	26,60	22,33	18,71							kN/m
Sl. Arm.	As	Mbal	1404,88	kNm	qbal						17,53	14,05	11,13	8,66								kN/m
	0	VRd	810,69	kN																		kN/m
Liner top	L 12,5 : 8	d	981	mm	ulev						-41,8	-44,1	-45,7	-46,5							mm	
					uoo						-2,1	-1,3	-0,1	1,4								mm
midtbund	0 34	At	5,61E+05	mm ²	u10kort						8,3	10,6	13,3	16,5							mm	
		y	530,1	mm	u10lang						19,1	24,4	30,6	38,0								mm
		lk	5,68E+10	mm ⁴																		
RB 50/108			g=	12,96	kN/m	længde:	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	26,4	m			
Armering:		MRd	4155,69	kNm	qRd								66,93	58,30	50,99	44,76					kN/m	
		Mrev	2763,33	kNm	qrev								40,16	34,42	29,57	25,42						kN/m
		Moo	2293,05	kNm	qoo								31,12	26,36	22,33	18,89						kN/m
Sl. Arm.	As	Mbal	1587,17	kNm	qbal							17,55	14,25	11,47	9,08							kN/m
	0	VRd	804,54	kN																		kN/m
Liner top	L 12,5 : 8	d	973	mm	ulev							-53,1	-55,8	-57,8	-59,0						mm	
					uoo							-4,2	-3,4	-2,2	-0,7							mm
midtbund	0 38	At	5,63E+05	mm ²	u10kort							10,5	13,3	16,5	20,2						mm	
		y	528,8	mm	u10lang							24,3	30,5	37,9	46,5							mm
		lk	5,70E+10	mm ⁴																		

Bæreevnetabel

22-06-2021

RB 50/120			g=	14,40	kN/m	længde:	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	26,4	m			
Armering:		MRd	3491,74	kNm	qRd				100,38	84,57	71,82	61,38								kN/m		
		Mrev	2283,45	kNm	qrev				60,66	50,32	41,98	35,15									kN/m	
		Moo	1749,41	kNm	qoo				43,11	35,19	28,80	23,56									kN/m	
Sl. Arm.	As	Mbal	1325,79	kNm	qbal				29,18	23,18	18,34	14,37									kN/m	
	0	VRd	925,94	kN																		
Liner top	L 12,5 : 4	d	1120	mm	ulev				-21,7	-23,8	-25,5	-26,8									mm	
			uoo						-5,7	-6,1	-6,4	-6,5										mm
midtbund	0 24	At	6,14E+05	mm ²	u10kort				2,7	3,6	4,8	6,2									mm	
		y	591,6	mm	u10lang				6,2	8,4	11,1	14,3										mm
		lk	7,58E+10	mm ⁴																		
RB 50/120			g=	14,40	kN/m	længde:	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	26,4	m			
Armering:		MRd	4101,41	kNm	qRd						86,87	74,61	64,44	55,93							kN/m	
		Mrev	2671,39	kNm	qrev						51,56	43,57	36,95	31,41								kN/m
		Moo	2119,10	kNm	qoo						37,92	31,59	26,34	21,94								kN/m
Sl. Arm.	As	Mbal	1537,53	kNm	qbal					23,56	18,97	15,16	11,96									kN/m
	0	VRd	917,68	kN																		
Liner top	L 12,5 : 6	d	1110	mm	ulev						-31,4	-33,6	-35,3	-36,5							mm	
			uoo								-5,7	-5,7	-5,5	-5,1								mm
midtbund	0 30	At	6,18E+05	mm ²	u10kort						4,7	6,1	7,8	9,8							mm	
		y	590,2	mm	u10lang						10,9	14,1	18,0	22,6								mm
		lk	7,68E+10	mm ⁴																		
RB 50/120			g=	14,40	kN/m	længde:	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	26,4	m			
Armering:		MRd	4633,42	kNm	qRd								74,67	65,05	56,91	49,95					kN/m	
		Mrev	3030,41	kNm	qrev									43,85	37,56	32,24	27,69					kN/m
		Moo	2462,02	kNm	qoo									32,93	27,82	23,49	19,79					kN/m
Sl. Arm.	As	Mbal	1715,97	kNm	qbal								18,59	15,02	12,01	9,43					kN/m	
	0	VRd	906,65	kN																		
Liner top	L 12,5 : 8	d	1097	mm	ulev									-41,6	-43,6	-45,0	-45,7				mm	
			uoo												-3,7	-3,1	-2,2	-1,0				mm
midtbund	0 36	At	6,22E+05	mm ²	u10kort									7,7	9,7	12,1	14,8				mm	
		y	589,1	mm	u10lang										17,8	22,4	27,8	34,1				mm
		lk	7,77E+10	mm ⁴																		
RB 50/120			g=	14,40	kN/m	længde:	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	26,4	m			
Armering:		MRd	4989,69	kNm	qRd											62,39	54,90	48,46	42,87		kN/m	
		Mrev	3309,55	kNm	qrev											36,53	31,57	27,29	23,59		kN/m	
		Moo	2732,65	kNm	qoo											27,65	23,55	20,02	16,97		kN/m	
Sl. Arm.	As	Mbal	1928,67	kNm	qbal											15,28	12,39	9,90	7,74		kN/m	
	0	VRd	901,14	kN																		
Liner top	L 12,5 : 8	d	1090	mm	ulev											-54,6	-56,4	-57,3	-57,4		mm	
			uoo														-5,4	-4,5	-3,3	-1,7		mm
midtbund	0 40	At	6,24E+05	mm ²	u10kort											12,0	14,8	18,0	21,6		mm	
		y	587,7	mm	u10lang												27,7	34,0	41,3	49,7		mm
		lk	7,80E+10	mm ⁴																		