

# Bæreevnetabel

22-06-2021

RB 60/72			g=	10,37	kN/m	længde:	8,4	9,6	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	m			
Armering:		MRd	1766,97	kNm	qRd					87,80	70,76	57,80	47,72							kN/m		
		Mrev	1156,26	kNm	qrev					53,87	42,72	34,24	27,64								kN/m	
		Moo	920,17	kNm	qoo					40,75	31,88	25,13	19,88								kN/m	
Sl. Arm.	As	Mbal	673,89	kNm	qbal					27,07	20,57	15,63	11,78								kN/m	
	0	VRd	585,24	kN																		
Liner	L 12,5 :	d	655	mm	ulev					-26,5	-30,1	-33,4	-36,0								mm	
		top	4		uoo					-5,7	-6,2	-6,5	-6,5									mm
midt	0	At	4,45E+05	mm <sup>2</sup>	u10kort					3,6	5,3	7,5	10,4								mm	
bund	22	y	354,0	mm	u10lang					8,4	12,2	17,3	23,9								mm	
		lk	1,98E+10	mm <sup>4</sup>																		
RB 60/72			g=	10,37	kN/m	længde:	8,4	9,6	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	m			
Armering:		MRd	1980,40	kNm	qRd						80,56	66,04	54,73	45,77							kN/m	
		Mrev	1296,05	kNm	qrev						49,14	39,63	32,24	26,37								kN/m
		Moo	1052,73	kNm	qoo						37,97	30,25	24,24	19,47								kN/m
Sl. Arm.	As	Mbal	727,88	kNm	qbal					23,05	17,71	13,56	10,26									kN/m
	0	VRd	581,74	kN																		
Liner	L 12,5 :	d	652	mm	ulev						-33,0	-36,8	-40,1	-42,5							mm	
		top	6		uoo						-3,6	-3,5	-2,9	-2,0								mm
midt	0	At	4,48E+05	mm <sup>2</sup>	u10kort					5,3	7,4	10,3	13,8								mm	
bund	26	y	353,6	mm	u10lang					12,1	17,1	23,6	31,7									mm
		lk	2,01E+10	mm <sup>4</sup>																		
RB 60/72			g=	10,37	kN/m	længde:	8,4	9,6	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	m			
Armering:		MRd	2187,67	kNm	qRd							74,03	61,55	51,64	43,65						kN/m	
		Mrev	1458,90	kNm	qrev							45,92	37,59	30,98	25,65							kN/m
		Moo	1210,75	kNm	qoo							36,34	29,43	23,95	19,53							kN/m
Sl. Arm.	As	Mbal	851,30	kNm	qbal						22,48	17,62	13,76	10,65								kN/m
	0	VRd	576,80	kN																		
Liner	L 12,5 :	d	646	mm	ulev							-45,4	-50,2	-54,3	-57,5						mm	
		top	6		uoo							-6,3	-6,3	-5,9	-5,1							mm
midt	0	At	4,50E+05	mm <sup>2</sup>	u10kort						7,4	10,2	13,7	18,1							mm	
bund	30	y	352,5	mm	u10lang						17,0	23,4	31,5	41,6								mm
		lk	2,02E+10	mm <sup>4</sup>																		
RB 60/72			g=	10,37	kN/m	længde:	8,4	9,6	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	m			
Armering:		MRd	2431,85	kNm	qRd									58,56	49,68	42,41					kN/m	
		Mrev	1654,65	kNm	qrev									36,53	30,49	25,54						kN/m
		Moo	1398,53	kNm	qoo									29,27	24,16	19,98						kN/m
Sl. Arm.	As	Mbal	939,17	kNm	qbal									16,25	12,82	10,01						kN/m
	0	VRd	568,46	kN																		
Liner	L 12,5 :	d	637	mm	ulev									-62,0	-66,5	-69,8					mm	
		top	8		uoo										-1,9	-0,5	1,5					mm
midt	0	At	4,54E+05	mm <sup>2</sup>	u10kort									13,5	17,8	23,1					mm	
bund	36	y	351,7	mm	u10lang									31,1	41,0	53,1						mm
		lk	2,04E+10	mm <sup>4</sup>																		

# Bæreevnetabel

22-06-2021

<b>RB 60/84</b>			g=	12,10	kN/m	længde:	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	m
Armering:		MRd	2317,38	kNm	qRd					77,31	64,08	53,59	45,12						kN/m
		Mrev	1520,01	kNm	qrev					46,55	37,87	30,99	25,44						kN/m
		Moo	1200,25	kNm	qoo					34,21	27,36	21,92	17,54						kN/m
Sl. Arm.	As	Mbal	898,84	kNm	qbal				22,58	17,45	13,38	10,10							kN/m
	0	VRd	690,49	kN															
Liner top	L 12,5 : 4	d	773	mm	ulev					-29,7	-32,5	-34,8	-36,3						mm
						uoo					-7,2	-7,6	-7,8	-7,7					
midtbund	0 24	At	5,18E+05	mm <sup>2</sup>	u10kort					4,8	6,5	8,8	11,6						mm
		y	413,2	mm	u10lang					10,9	15,1	20,3	26,7						
		lk	3,14E+10	mm <sup>4</sup>															
<b>RB 60/84</b>			g=	12,10	kN/m	længde:	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	m
Armering:		MRd	2582,79	kNm	qRd						72,81	61,11	51,68	43,95					kN/m
		Mrev	1689,28	kNm	qrev						43,44	35,79	29,61	24,56					kN/m
		Moo	1360,42	kNm	qoo						32,63	26,46	21,49	17,43					kN/m
Sl. Arm.	As	Mbal	967,68	kNm	qbal					19,71	15,33	11,80	8,90						kN/m
	0	VRd	687,51	kN															
Liner top	L 12,5 : 6	d	770	mm	ulev						-35,8	-38,7	-40,8	-42,1					mm
						uoo						-5,2	-5,0	-4,4	-3,5				
midtbund	0 28	At	5,21E+05	mm <sup>2</sup>	u10kort						6,5	8,7	11,5	14,9					mm
		y	412,7	mm	u10lang						14,9	20,0	26,4	34,2					
		lk	3,18E+10	mm <sup>4</sup>															
<b>RB 60/84</b>			g=	12,10	kN/m	længde:	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	m
Armering:		MRd	2927,11	kNm	qRd							70,87	60,18	51,43	44,17				kN/m
		Mrev	1934,35	kNm	qrev							42,73	35,67	29,88	25,09				kN/m
		Moo	1595,01	kNm	qoo							33,11	27,29	22,52	18,57				kN/m
Sl. Arm.	As	Mbal	1086,93	kNm	qbal						18,71	14,74	11,49	8,80					kN/m
	0	VRd	678,06	kN															
Liner top	L 12,5 : 8	d	759	mm	ulev							-45,5	-48,7	-51,1	-52,5				mm
						uoo							-2,7	-1,8	-0,6	1,2			
midtbund	0 34	At	5,25E+05	mm <sup>2</sup>	u10kort							8,6	11,3	14,7	18,7				mm
		y	411,8	mm	u10lang							19,8	26,1	33,8	43,0				
		lk	3,21E+10	mm <sup>4</sup>															
<b>RB 60/84</b>			g=	12,10	kN/m	længde:	10,8	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	m
Armering:		MRd	3155,90	kNm	qRd									65,83	56,39	48,57	42,02		kN/m
		Mrev	2123,15	kNm	qrev									40,33	33,98	28,72	24,31		kN/m
		Moo	1778,24	kNm	qoo									31,81	26,49	22,09	18,40		kN/m
Sl. Arm.	As	Mbal	1229,17	kNm	qbal									18,25	14,58	11,53	8,98		kN/m
	0	VRd	673,41	kN															
Liner top	L 12,5 : 8	d	754	mm	ulev									-58,3	-62,1	-64,9	-66,7		mm
						uoo									-4,9	-4,1	-2,8	-1,0	
midtbund	0 38	At	5,27E+05	mm <sup>2</sup>	u10kort									11,3	14,6	18,6	23,4		mm
		y	410,7	mm	u10lang										26,0	33,6	42,8	53,8	
		lk	3,23E+10	mm <sup>4</sup>															

# Bæreevnetabel

22-06-2021

RB 60/96			g=	13,82	kN/m	længde:	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	m			
Armering:		MRd	2912,49	kNm	qRd					81,92	68,73	58,09								kN/m		
		Mrev	1882,05	kNm	qrev					48,04	39,52	32,65									kN/m	
		Moo	1463,65	kNm	qoo					34,29	27,66	22,32									kN/m	
Sl. Arm.	As	Mbal	1042,66	kNm	qbal					20,45	15,73	11,92									kN/m	
	0	VRd	796,03	kN																		
Liner top	L 12,5 : 6	d	892	mm	ulev					-25,4	-27,2	-28,5									mm	
			uoo							-3,6	-3,4	-2,9										mm
midtbund	0 26	At	5,92E+05	mm <sup>2</sup>	u10kort					4,4	5,9	7,8									mm	
		y	473,1	mm	u10lang					10,1	13,5	17,8										mm
		lk	4,70E+10	mm <sup>4</sup>																		
RB 60/96			g=	13,82	kN/m	længde:	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	m			
Armering:		MRd	3242,42	kNm	qRd							78,08	66,24	56,54							kN/m	
		Mrev	2119,87	kNm	qrev							46,26	38,52	32,18								kN/m
		Moo	1693,71	kNm	qoo							34,18	28,00	22,93								kN/m
Sl. Arm.	As	Mbal	1228,52	kNm	qbal						21,00	16,51	12,84								kN/m	
	0	VRd	791,09	kN																		
Liner top	L 12,5 : 6	d	886	mm	ulev						-34,8	-37,2	-38,9								mm	
			uoo									-6,1	-6,1	-5,8								mm
midtbund	0 30	At	5,94E+05	mm <sup>2</sup>	u10kort						5,9	7,7	10,0								mm	
		y	471,9	mm	u10lang						13,5	17,7	23,0									mm
		lk	4,73E+10	mm <sup>4</sup>																		
RB 60/96			g=	13,82	kN/m	længde:	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	m			
Armering:		MRd	3665,92	kNm	qRd								76,69	65,73	56,65	49,03					kN/m	
		Mrev	2412,94	kNm	qrev								45,75	38,54	32,56	27,55					kN/m	
		Moo	1973,73	kNm	qoo								34,91	29,01	24,12	20,02					kN/m	
Sl. Arm.	As	Mbal	1377,86	kNm	qbal							20,20	16,08	12,66	9,80						kN/m	
	0	VRd	782,75	kN																		
Liner top	L 12,5 : 8	d	877	mm	ulev							-43,8	-46,5	-48,5	-49,7						mm	
			uoo										-4,4	-3,9	-3,0	-1,7						mm
midtbund	0 36	At	5,98E+05	mm <sup>2</sup>	u10kort							7,6	9,9	12,6	15,8						mm	
		y	470,9	mm	u10lang							17,5	22,7	28,9	36,4							mm
		lk	4,78E+10	mm <sup>4</sup>																		
RB 60/96			g=	13,82	kN/m	længde:	12,0	13,2	14,4	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	m			
Armering:		MRd	4054,13	kNm	qRd									74,16	64,11	55,69	48,57				kN/m	
		Mrev	2706,67	kNm	qrev									44,91	38,21	32,59	27,83					kN/m
		Moo	2254,41	kNm	qoo									35,10	29,51	24,83	20,87					kN/m
Sl. Arm.	As	Mbal	1525,20	kNm	qbal								19,27	15,50	12,33	9,65					kN/m	
	0	VRd	776,80	kN																		
Liner top	L 12,5 : 10	d	870	mm	ulev								-53,8	-56,8	-59,0	-60,2					mm	
			uoo											-1,9	-0,7	0,8	2,8					mm
midtbund	0 42	At	6,02E+05	mm <sup>2</sup>	u10kort								9,8	12,4	15,6	19,4					mm	
		y	469,9	mm	u10lang									22,4	28,6	36,0	44,6					mm
		lk	4,83E+10	mm <sup>4</sup>																		

# Bæreevnetabel

22-06-2021

<b>RB 60/108</b>			g=	15,55	kN/m	længde:	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	26,4	27,6	28,8	m		
Armering:		MRd	3970,93	kNm	qRd			97,00	82,50	70,62	60,78									kN/m	
		Mrev	2597,97	kNm	qrev			58,09	48,60	40,83	34,39										kN/m
		Moo	2062,05	kNm	qoo			42,90	35,36	29,20	24,09										kN/m
Sl. Arm.	As	Mbal	1520,60	kNm	qbal			27,55	21,99	17,45	13,68									kN/m	
	0	VRd	895,11	kN																	kN/m
Liner top	L 12,5 : 6	d	1003	mm	ulev			-31,6	-34,1	-36,1	-37,6									mm	
			uoo					-6,7	-7,0	-7,0	-6,8										mm
midtbund	0 32	At	6,67E+05	mm <sup>2</sup>	u10kort			4,1	5,4	7,0	9,0									mm	
		y	531,0	mm	u10lang			9,5	12,5	16,2	20,6										mm
		lk	6,71E+10	mm <sup>4</sup>																	mm
<b>RB 60/108</b>			g=	15,55	kN/m	længde:	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	26,4	27,6	28,8	m		
Armering:		MRd	4473,71	kNm	qRd					81,53	70,45	61,16	53,30							kN/m	
		Mrev	2938,93	kNm	qrev					48,23	40,94	34,84	29,68								kN/m
		Moo	2387,37	kNm	qoo					36,26	30,34	25,38	21,19								kN/m
Sl. Arm.	As	Mbal	1700,08	kNm	qbal					21,34	17,13	13,60	10,61								kN/m
	0	VRd	887,70	kN																	kN/m
Liner top	L 12,5 : 8	d	994	mm	ulev					-42,5	-44,8	-46,5	-47,4							mm	
			uoo							-5,8	-5,4	-4,8	-3,8								mm
midtbund	0 38	At	6,71E+05	mm <sup>2</sup>	u10kort					7,0	8,9	11,1	13,8							mm	
		y	530,0	mm	u10lang					16,0	20,4	25,6	31,8								mm
		lk	6,79E+10	mm <sup>4</sup>																	mm
<b>RB 60/108</b>			g=	15,55	kN/m	længde:	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	26,4	27,6	28,8	m		
Armering:		MRd	5077,84	kNm	qRd							71,52	62,59	54,97	48,42					kN/m	
		Mrev	3391,81	kNm	qrev							42,61	36,65	31,56	27,18						kN/m
		Moo	2821,76	kNm	qoo							32,83	27,87	23,64	20,00						kN/m
Sl. Arm.	As	Mbal	1958,12	kNm	qbal							18,02	14,58	11,64	9,12						kN/m
	0	VRd	877,73	kN																	kN/m
Liner top	L 12,5 : 10	d	983	mm	ulev							-58,1	-60,4	-61,9	-62,3					mm	
			uoo										-4,1	-3,1	-1,6	0,3					mm
midtbund	0 46	At	6,76E+05	mm <sup>2</sup>	u10kort							11,0	13,7	16,8	20,4					mm	
		y	528,5	mm	u10lang							25,3	31,4	38,6	46,9						mm
		lk	6,87E+10	mm <sup>4</sup>																	mm
<b>RB 60/108</b>			g=	15,55	kN/m	længde:	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	26,4	27,6	28,8	m		
Armering:		MRd	5599,49	kNm	qRd									62,22	54,99	48,72	43,25			kN/m	
		Mrev	3823,69	kNm	qrev									37,55	32,62	28,34	24,60				kN/m
		Moo	3236,55	kNm	qoo									29,40	25,22	21,60	18,44				kN/m
Sl. Arm.	As	Mbal	2192,24	kNm	qbal									14,90	12,07	9,61	7,47				kN/m
	0	VRd	868,07	kN																	kN/m
Liner top	L 12,5 : 12	d	972	mm	ulev									-74,7	-76,5	-77,2	-76,7			mm	
			uoo												0,2	2,2	4,8	7,9			mm
midtbund	0 54	At	6,81E+05	mm <sup>2</sup>	u10kort									16,6	20,2	24,3	29,0			mm	
		y	527,1	mm	u10lang										38,1	46,4	55,9	66,7			mm
		lk	6,95E+10	mm <sup>4</sup>																	mm

# Bæreevnetabel

22-06-2021

RB 60/120			g=	17,28	kN/m	længde:	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	26,4	27,6	28,8	m			
Armering:		MRd	5316,80	kNm	qRd				114,00	98,10	84,93									kN/m		
		Mrev	3451,48	kNm	qrev				67,94	57,62	49,07										kN/m	
		Moo	2771,77	kNm	qoo				51,16	42,87	36,00										kN/m	
Sl. Arm.	As	Mbal	1910,52	kNm	qbal				29,89	24,18	19,45										kN/m	
	0	VRd	1103,20	kN																		
Liner top	L 12,5 : 10	d	1112	mm	ulev				-32,6	-35,0	-37,0										mm	
		uoo							-2,9	-2,6	-2,0											mm
midtbund	0 40	At	7,45E+05	mm <sup>2</sup>	u10kort				3,9	5,1	6,5										mm	
		y	589,9	mm	u10lang				9,0	11,7	14,8											mm
		lk	9,32E+10	mm <sup>4</sup>																		
RB 60/120			g=	17,28	kN/m	længde:	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	26,4	27,6	28,8	m			
Armering:		MRd	5513,61	kNm	qRd						88,71	77,26	67,57								kN/m	
		Mrev	3602,03	kNm	qrev						51,96	44,48	38,15									kN/m
		Moo	2917,33	kNm	qoo						38,80	32,74	27,62									kN/m
Sl. Arm.	As	Mbal	2027,67	kNm	qbal						21,70	17,49	13,92									kN/m
	0	VRd	1101,21	kN																		
Liner top	L 12,5 : 10	d	1110	mm	ulev						-40,5	-42,4	-43,7								mm	
		uoo									-3,3	-2,6	-1,7									mm
midtbund	0 42	At	7,46E+05	mm <sup>2</sup>	u10kort						6,4	8,1	10,1								mm	
		y	589,3	mm	u10lang						14,8	18,6	23,1									mm
		lk	9,34E+10	mm <sup>4</sup>																		
RB 60/120			g=	17,28	kN/m	længde:	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	26,4	27,6	28,8	m			
Armering:		MRd	6183,04	kNm	qRd							88,74	77,87	68,60	60,61						kN/m	
		Mrev	4102,84	kNm	qrev							53,07	45,86	39,70	34,41							kN/m
		Moo	3397,74	kNm	qoo							40,98	35,01	29,91	25,52							kN/m
Sl. Arm.	As	Mbal	2310,11	kNm	qbal							22,33	18,27	14,80	11,82							kN/m
	0	VRd	1088,51	kN																		
Liner top	L 12,5 : 12	d	1097	mm	ulev							-51,6	-54,0	-55,7	-56,7						mm	
		uoo										-2,0	-1,0	0,4	2,1							mm
midtbund	0 50	At	7,51E+05	mm <sup>2</sup>	u10kort							8,0	9,9	12,2	14,8						mm	
		y	587,8	mm	u10lang							18,4	22,9	28,1	34,1							mm
		lk	9,44E+10	mm <sup>4</sup>																		
RB 60/120			g=	17,28	kN/m	længde:	15,6	16,8	18,0	19,2	20,4	21,6	22,8	24,0	25,2	26,4	27,6	28,8	m			
Armering:		MRd	6696,67	kNm	qRd										67,08	59,59	53,05	47,31			kN/m	
		Mrev	4538,49	kNm	qrev										39,89	34,81	30,38	26,49				kN/m
		Moo	3819,41	kNm	qoo										30,84	26,56	22,83	19,56				kN/m
Sl. Arm.	As	Mbal	2643,59	kNm	qbal										16,02	13,06	10,48	8,22				kN/m
	0	VRd	1083,85	kN																		
Liner top	L 12,5 : 12	d	1093	mm	ulev										-71,8	-73,3	-73,9	-73,4			mm	
		uoo													-3,1	-1,5	0,5	3,0				mm
midtbund	0 56	At	7,54E+05	mm <sup>2</sup>	u10kort										14,7	17,8	21,2	25,2			mm	
		y	586,0	mm	u10lang										33,9	40,8	48,8	57,9				mm
		lk	9,50E+10	mm <sup>4</sup>																		